

DECLARATION OF PERFORMANCE

LE_0892165_00_M_Acryldichtstoff

This is an English translation of the original German wording. In cases of doubt, the German version applies.

1. Unique identification code of the product type:

acrylic sealant

art. no. 0892165; 089216901; 08921691

EN 15651-1:F-INT

2. Type, batch, or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

batch number: see packaging

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

joint sealants for facade elements

EN 15651-1:F-INT

4. Name, registered trade name, or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Adolf Würth GmbH & Co. KG

Reinhold-Würth-Str. 12-17

D-74653 Künzelsau

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

Not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4

System 3 for testing fire behavior

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

The notified body SKZ TeConA GmbH (1213) conducted the System 3 test for fire behavior and determined the following: test report

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not relevant

9. Declared performance:

Conditioning: method A (in accordance with ISO 8339)

Base material: mortar M2 (without primer)

Essential characteristics	Performance	Harmonized technical specification
Fire behavior	Class E	EN 15651-1:2012
Release of chemicals harmful to health and/or the environment	See safety data sheet	
Non-sag property	≤ 5 mm	
Loss in volume	≤ 45%	
Tensile behavior (i.e. stretch behavior): - After immersion in water (at 23 °C), (plastic)	≥ 25%	
Durability	Passed	

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not relevant

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Marcel Strobel
(Head of Product Management)
Künzelsau, 8/13/2014



Dr.-Ing. Siegfried Beichter
(Head of Quality, Authorized Signatory)