

TECHNICAL DATA SHEET

0893 050 004

Container size: 400ml

Cut+Cool drilling and cutting oil

Multi cutting oil for light to medium machining work

Fields of application:

For drilling, thread cutting, thread moulding, lathing, countersinking, grinding and sawing.

Ideally suited for stainless steel, but also for high-alloy steels, constructional steels, non-ferrous and precious metals. Can also be used as a preservative agent on semi-finished/finished parts and machine parts, and can be used as gun oil.

Properties:

- Universal application
- Cools when sprayed on (protects tools, prevents small material particles welding to the cutting edge)
- Good penetrating properties
- Excellent corrosion protection (without re-treatment)
- Free from silicone, chlorine, resin and acids

Application:

Spray workpiece from a distance of 20 – 30 cm.

Technical data:

PU	1
Contents	400 ML
Container	Aerosol can
Colour	Reddish
Smell/fragrance	Perfumed
Chemical basis	Mineral oil
Temperature range	-15 °C to 150 °C
Density (at 20 °C)	0.825g/ml
Pour point	-13 °C
Shelf life from production	24 months

TECHNICAL DATA SHEET

Notes:

No further information.

We provide this advice based on our own tests and experience and to the best of our knowledge. We assume no liability for the application results in individual cases, however, due to the large number of applications and the storage and application conditions that lie outside the scope of our influence.

This also applies to the use of the non-binding technical and commercial customer services provided by us. We always recommend that you conduct your own tests. We guarantee the consistent quality of our products. We reserve the right to make technical changes and to further develop our products.