

# TECHNICAL DATA SHEET

**0893 32ff, 0893 33ff, 0893 34ff, 0893 35ff, 0893 36ff**

## **Lacquer sprays**

Durable nitroalkydal quality at a high technical level.

## **Fields of application:**

Repair painting, protection from corrosion and weathering and for surface refinement.

**Surfaces:** wood, metal, fabric, stone, ceramics, glass, paintable plastic, concrete, baskets.

## **Properties:**

- Fast-drying
- Excellent coverage
- Extremely weather resistant
- Good coverage
- Sprays well
- Closed surface
- Easy to apply
- Good resistance to petrol
- Hard surface, not susceptible to scratching
- High solids content
- Produces high yield

## **Application:**

Before using the spray can, carefully read and pay attention to warning texts! Spray only in dry weather and in wind-protected places and well-ventilated spaces. Temperatures preferably between + 10°C and + 27°C. Shake can for at least three minutes before use; only doing so guarantees optimum application. The application surface must be clean, dry and free from grease. Remove rust and old paint; sand and prime. Do a test spray and compare the colour. Spraying distance: approx. 20–25 cm. Cover the surrounding area to prevent the spray mist from depositing. Turn the can over after use and spray until the valve is empty.

# TECHNICAL DATA SHEET

## Technical data:

Colours:	
High-gloss colours	27
Satin finish colours	16
Matt colours	3
Spreading rate	1 - 1,5m <sup>2</sup>
Paint type	Nitroalkydals
Heavy metal free	Yes
CFC-free	Yes
Temperature resistance	Up to +80°C
Shelf life	36 months (at +15°C to 25°C and 60% rel. hum.)

This advice is based on our own research and experience. It is presented in good faith and may be considered reliable. However, due to the diverse processing, application and handling possibilities the information provided may not be considered legally binding. The same applies to the information provided by our technical and commercial customer service.

We recommend the users of our products to perform their own tests in order to determine whether our products are appropriate for the respective use and environment. We guarantee the consistent quality of our products. We reserve the right to implement technical changes and improvements.